IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A frequency synthesizer comprising:

å fixed frequency generator configured to generate a fixed frequency signal; and å variable frequency generator configured to generate a variable frequency signal; wherein:

the variable frequency signal is generated independently of the fixed frequency signal; and

the fixed frequency signal and the variable frequency signal are combined to provide a fast-hopping carrier frequency signal, wherein the carrier frequency signal switches from a first wireless channel to a second wireless channel and information is exchanged using the first wireless channel and the second wireless channel.

- (Original) A frequency synthesizer as recited in Claim 1 wherein the variable frequency generator has an output that is not connected back to other components of the variable frequency generator.
- 3. (Previously presented) A frequency synthesizer as recited in Claim 1 wherein the variable frequency generator settles substantially faster than the fixed frequency generator.
- 4. (Original) A frequency synthesizer as recited in Claim 1 further comprising a mixer configured to combine the fixed frequency signal and the variable frequency signal.
- (Original) A frequency synthesizer as recited in Claim 1 wherein the frequency synthesizer is included in a transceiver.

- 6. (Original) A frequency synthesizer as recited in Claim 1 wherein the frequency synthesizer is used in an ultra-wide band (UWB) system.
- 7. (Original) A frequency synthesizer as recited in Claim 1 wherein the variable frequency generator includes a signal generator and a fast switching component for configuring the signal generator.
- 8. (Original) A frequency synthesizer as recited in Claim 1 wherein the variable frequency generator includes a signal generator and a fast switching component for operating on a plurality of generated signals by the signal generator.
- 9. (Withdrawn) A frequency synthesizer as recited in Claim 1 wherein the variable frequency generator includes a direct digital synthesizer.
- 10. (Withdrawn) A frequency synthesizer as recited in Claim 1 wherein the variable frequency generator includes a direct digital synthesizer comprising:
 - a digital to analog converter (DAC);
 - a parameter generator coupled to the DAC;
 - wherein the parameter generator is configured to provide a configuration parameter to the DAC, and the DAC is configured to generate the variable signal based on the configuration parameter.
- 11. (Withdrawn) A frequency synthesizer as recited in Claim 10 wherein the parameter generator includes a lookup table.

- 12. (Withdrawn) A frequency synthesizer as recited in Claim 1 wherein the variable frequency generator includes an injection-locked synthesizer; and the fixed frequency signal is an input to the injection-locked synthesizer.
- 13. (Withdrawn) A frequency synthesizer as recited in Claim 1 wherein the variable frequency generator includes an injection-locked synthesizer comprising:

à ring oscillator having a plurality of stages, where each of the plurality of stages has a stage output; and

a logic processor configured to perform operations on at least one of the stage outputs to obtain the variable frequency signal.

- 14. (Withdrawn) A frequency synthesizer as recited in Claim 13, wherein the logic processor is configured to perform an exclusive-or operation.
- 15. (Withdrawn) A frequency synthesizer as recited in Claim 1 wherein the variable frequency generator includes a delay locked loop.
- 16. (Withdrawn) A frequency synthesizer as recited in Claim 1 wherein the variable frequency generator includes:

a delay locked loop having a plurality of stages, wherein each of the plurality of stages has a stage output; and

a logic processor configured to perform an operation on at least one of the stage outputs to obtain the variable frequency signal.

17. (Withdrawn) A fast-hopping frequency synthesizer comprising:

a voltage controlled oscillator (VCO) configured to generate a fast-hopping output signal; and

à VCO controller coupled to the VCO for providing a first VCO configuration and a second VCO configuration;

wherein the VCO controller switches between the first VCO configuration and the second VCO configuration at a fast-hop switching speed.

- 18. (Withdrawn) A frequency synthesizer as recited in Claim 17 wherein the fast-hopping output signal is directly synthesized.
- 19. (Withdrawn) A frequency synthesizer as recited in Claim 17 wherein the VCO controller comprises a memory for storing a configuration used to determine a VCO input.
- 20. (Withdrawn) A frequency synthesizer as recited in Claim 17 further comprising a feedback loop coupled to the VCO, configured to adapt the VCO to provide a fast hopping signal.
- 21. (Withdrawn) A frequency synthesizer as recited in Claim 17 further comprising a feedback loop coupled to the VCO, configured to adapt the VCO to provide a fast hopping signal;

wherein the feedback loop comprises a frequency detector configured to provide a feedback to the VCO controller.

22. (Withdrawn) A frequency synthesizer as recited in Claim 17 further comprising a feedback loop coupled to the VCO, configured to adapt the VCO to provide a fast hopping signal;

wherein the feedback loop comprises a frequency detector configured to provide a feedback to the VCO controller, and the frequency detector detects a difference between a divided output and a divided reference frequency.

- 23. (Withdrawn) A frequency synthesizer as recited in Claim 17 wherein the VCO controller comprises a digital to analog converter configured to control the VCO input.
- 24. (Withdrawn) A frequency synthesizer as recited in Claim 17 wherein the VCO controller comprises a switch cap digital to analog converter configured to control the voltage controlled oscillator input.
- 25. (Currently amended) A method for synthesizing a fast hopping carrier frequency signal, comprising:

generating a fixed frequency signal;

generating a variable frequency signal, wherein the variable frequency signal is generated independently of the fixed frequency signal; and

combining the fixed frequency signal and the variable frequency signal to provide the fast hopping carrier frequency signal, wherein the carrier frequency signal switches from a first wireless channel to a second wireless channel and information is exchanged using the first wireless channel and the second wireless channel.

26. (Withdrawn) A method for synthesizing a fast-hopping signal, comprising:

providing a first voltage controlled oscillator (VCO) configuration to a VCO; switching to a second VCO configuration at a fast-hopping switching speed; and generating the fast-hopping signal.